

Derby

Classification ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile

Size* 6" x 36" / 152.4mm x 914.4mm

Overall Thickness* .080"/2.0mm

Wearlayer 8 mil / 0.20mm - PVC

Construction Layered plank consisting of wearlayer, film and backing.

Edge Square

Standard Colors 6" x 36": 6 standard colors

Glue Down Installation Method

Wear Limited Warranty 20-Year Residential / 10-Year Light Commercial

This product contains a minimum 50% recycled content.100% recyclable post-use. **Recycled Content**

6" x 36": **Packaging**

> 27 ft² (2.51 m²) per carton 18 pieces per carton 108 cartons per pallet 18 pallets per 20' container

Weight Per Carton 20.95lbs / 9.5kg

Product Testing

Chemical Resistance ASTM F 925 Passed

Critical Radiant Flux Class I, CRF ≥0.45 ASTM E 648-06

Dimensional Stability Passed **ASTM F 2199** Flexibility ASTM F 137 Passed Resistance to Heat **ASTM F 1514** Passed Resistance to Light Passed **ASTM F 1515** Passed **Smoke Density** ASTM E 662-06 Static Load Limit **ASTM F 970** Passed **Thickness** ASTM F 386 Passed



*All measurements are nominal.

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

