

# ENGINEERED FLOORS 2 mm/8 mil LVP

INVENTORY STYLE #	V0200
STYLE NAME(s)	Gallatin
SELLING STYLE #s)	L2008
TOTAL # SKU'S (COLORS)	8



PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS	DETAILS	ADDITIONAL INFORMATION
Thickness	2mm (0.079")	
Wear Layer	8mil (0.20mm)	
Glass Fiber	No	
Finish / Coating	Enhanced UV Urethane w/ Ceramic Micro Bead Technology	
Nominal Dimensions (inches)	7" x 48"	
Actual Dimensions (inches & mm)	7" x 48" (177.8mm x 1219.2mm)	
Pattern Repeat (measurement / # of pieces)	Random Wood Pattern	8 different visuals per carton
Micro-Beveled	No	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Backing Class	Commercial Grade	
Gloss Level (if known)	Matte Finish	
Traffic Use	Residential	
Added Antimicrobial	Yes	
FloorScore Certified (Y/N)	Yes	
Backstamp Info	Machine Directional Arrow	
PACKAGING SPEC'S	DETAILS	ADDITIONAL INFORMATION
Pallet Dimensions (LxWxH)	1000mm x 1250mm	
Square feet per plank	2.33	
Square feet per carton	51.24	
Square feet per pallet	2,562	
Square feet per container	51,240	20 foot container
Weight per plank/tile (lbs/plank)	1.67	
Weight per carton (lbs)	36.82	
Weight per pallet (lbs)	1,878	
Weight per container (lbs)	38140	
Weight per sq ft (lbs)	0.72	
Pieces per box	22	
Boxes per pallet	50	
Box Type	brown carton	
Pallets per container	20	
Boxes per container	1000	
PRODUCT PERFORMANCE / TESTING	PERFORMANCE	ASTM REQUIREMENT
ASTM F2055 Size and Tolerance	Passes	As specified 0.016 in./lin. ft.
ASTM F386 Thickness	Passes	As specified 0.005 in. lin. ft.
ASTM F2055 Squareness	Passes	Max. 0.010 in.
ASTM F1914 Residual Indentation	Passes	Avg. < 8%
ASTM F137 Flexibility	Passes 6mm mandrel	1 in (25.4mm) mandrel/no crack or break
ASTM F2199 Dimensional Stability	Passes	< 0.020 in./ft.
ASTM F925 Chemical Resistance	Passes	No Change/Slight Change
ASTM F1514 Resistance to Heat	Passes	< 8 (delta E) avg.
ASTM F1515 Resistance to Light	Passes	< 8 (delta E) avg.
ASTM E648 Critical Radiant Flux	Class 1	Class 1 (< 0.45 W/cm <sup>2</sup> )
ASTM E662 Optical Smoke Density	Passes < 450	< 450
ASTM C1028 Slip Resistance	Passes	ADA Compliant (> 0.50)
ASTM F970 Static Load	Passes	250 psi (< 0.005")
TECHNICAL INFORMATION / DOCUMENTS	DETAILS	ADDITIONAL INFORMATION
Product Warranty	10-year Residential	Manufacturing defects/wear only
Installation Method	Full Spread	
Approved Installation Methods	Above, Below, and On-Grade	
Approved Adhesives	XL Brands Stix Essential RES Spray, Mapei 373, Taylor Pinnacle (2091), Taylor Dynamic (2098)	
Polish Required (Y/N)	None	