



LEVEL PLUS

Specification Sheet



PRODUCT INFORMATION

Construction	Sheet Vinyl
Recommended Usage	Residential
Total Thickness	65 gauge
Wear Layer Thickness	10 mils
Wear Layer Treatment	SuperGuard
Finish	Mechanically Embossed

SIZE & PACKING

Width	12'
Standard Length	150 lineal ft.
Average Weight of Standard Roll	520 lbs

TECHNICAL INFORMATION

ASTM 1303	Type 1, Grade 3
ASTM F1914 Residual Indentation	.006
ASTM F137 Flexibility	10 mm Passes
ASTM F1514 Resistance to Heat	Passes
ASTM F1515 Resistance to Light	Passes
ASTM F925 Resistance to Chemicals	Very Good
ASTM E492 Sound Transmission	IIC 55
ASTM E648 Radiant Panel	Class I
ASTM C 1028-96 Static Coefficient of Friction	0.77
ASTM E662-03 Smoke Density (flaming)	Passes 450 or less
ASTM E662-09 Smoke Density (non-flaming)	Passes 450 or less

WARRANTY Limited 10 Years Property Management Warranty

COLLECTION Project Solutions



IVC US, Inc. | 101 IVC Drive | Dalton, GA 30721
T 1-888-225-8287 | F 1-888-601-8544
www.ivcfloors.com

V11.16