



SHERWOOD
575

SPECS

MARKETING BRAND:

STYLE NAME:
STYLE NUMBER:
FIBER TYPE:
DYE METHOD:
CONSTRUCTION:
TUFTED WEIGHT OZ SQ/YD:
TOTAL FINISHED WEIGHT OZ SQ/YD:
AVERAGE DENSITY:
AVERAGE YARN TWIST PER INCH:
GAUGE:
STITCHES PER INCH:
STAGGERED STITCH:
AVERAGE PILE HEIGHT:
PATTERN REPEAT:
WIDTH:
PRIMARY BACKING:
SECONDARY BACKING:

BEAULIEU

SHERWOOD
575
100% HIGH UV BCF SOLUTION DYED OLEFIN FIBER
SOLUTION
TIP SHEARED LOOP
13
N/A
N/A
N/A
5/32
7
N/A
3/8" X 1/8"
N/A
12'
WOVEN POLYPROPYLENE
AB- WOVEN POLYPROPYLENE

FEATURES

CRI INDOOR AIR QUALITY GREEN LABEL PLUS NUMBER
STAIN PROTECTION:
SOIL PROTECTION:
MAGIC FRESH:
SILVER RELEASE:
HUD/FHA CERTIFICATION NUMBER:
TYPE & CLASS:

1478
N/A
N/A
N/A
N/A
N/A
N/A

TESTS

PAR-ASTM D 5252:
FLAME RESISTANCE-DOC FF-1-70 PILL TEST: Pass
FLOORING RADIANT PANEL-ASTM E 648 CLASS:
RESULTS:
SMOKE DENSITY- ASTM E 662:
STATIC PROPENSITY – AATCC 134:

N/A
PASS
N/A
N/A
N/A
N/A

WARRANTIES

WEAR/DURABILITY:
FADE:

3 YEAR INDOOR / 2 OUTDOOR LIMITED RESIDENTIAL
3 YEAR INDOOR / 2 YEAR OUTDOOR LIMITED RESIDENTIAL

2/14/2017

5752, 5753. 5754